Revision History for //depot/main/redirector/Mailbox/CalSyncState.cpp

| View | Sync | Diff Revs | Diff vs Client File | Describe Changelist | Help |

Revision ▼	File Name	Changelist	Date	Description
1	//depot/m...	2357	2000/01/14	Merge in calendar sync changes from Continuus.

Actions...

```cpp
#include "CalSyncState.h"
#include "debug.h"
#include "globals.h"
#include "sha.h"

static char * BlackBerryFolderName          = "BlackBerryHandheldInfo";
static char * BlackBerryCalStateFolderName  = "BlackBerryCalSyncState";
static char * MSG_CLASS_CAL_SYNC            = "RIM.BlackBerry.CalSync";
static char * MSG_CLASS_SYNC_TIMESTAMP     = "RIM.BlackBerry.SyncTimestamp";

// Base tag for new properties
unsigned long const      BASE_PM_ID          = 0x6200;

//////////////////////////////////////////////////////////////////
// Constructor/Destructor
//////////////////////////////////////////////////////////////////

// *** CalSyncState ***
// Purpose: Constructor for the CalSyncState class.
// Parameters:  [IN] pMailbox = pointer to user mailbox object.
//              [IN] lpStore = pointer to Exchange message store object.
//              [IN] lpCalendarFolder = pointer to user's Calendar folder.
// Returns:
//
CalSyncState::CalSyncState( MAPIMailbox *pMailbox, LPMDB lpStore, LPMAPIFOLDER lpCalendarFolder )
{
    // Initialize member variables
    m_pMDB = lpStore;
    m_pMailbox = pMailbox;
    m_pCalendarFolder = lpCalendarFolder;
    m_pStateFolder = 0;

    // Initialize property tags used to save state information into message
    PR_RIM_SYNC_ENTRYID       = PROP_TAG (PT_BINARY, (BASE_PM_ID));
    PR_RIM_SYNC_SOURCE_KEY    = PROP_TAG (PT_BINARY, (BASE_PM_ID + 0x0001));
    PR_RIM_SYNC_INSTANCE_DATE = PROP_TAG (PT_SYSTIME, (BASE_PM_ID + 0x0002));
    PR_RIM_SYNC_REF_ID        = PROP_TAG (PT_LONG, (BASE_PM_ID + 0x0003));
    PR_RIM_SYNC_PARENT_REF_ID = PROP_TAG (PT_LONG, (BASE_PM_ID + 0x0004));
    PR_RIM_SYNC_LAST_MODIFIED = PROP_TAG (PT_SYSTIME, (BASE_PM_ID + 0x0005));
    PR_RIM_SYNC_DEVICE_SEQNUM = PROP_TAG (PT_LONG, (BASE_PM_ID + 0x0006));
    PR_RIM_SYNC_DESKTOP_SEQNUM = PROP_TAG (PT_LONG, (BASE_PM_ID + 0x0007));
    PR_RIM_SYNC_DELETE_IN_PROGRESS = PROP_TAG (PT_BOOLEAN, (BASE_PM_ID + 0x0008));
    PR_RIM_SYNC_MODIFY_IN_PROGRESS = PROP_TAG (PT_BOOLEAN, (BASE_PM_ID + 0x0009));
```